

OR1708 Small metal tag specifications

Introduction: Small metal tag, the product is 100% tested by the European imported label consistency test system to ensure stability during use. The product material has passed environmental certification. The product has been widely used and verified by well-known customers at home and abroad. Good weather resistance, long reading distance; mainly used for asset management, gun management, medical device management, tool management, etc. Labels can be personalized, such as pre-written codes, laser coding, printed LOGO, color customization.

| Item | Parameter |
|-------------------|--|
| Protocol standard | EPC Class1 Gen2; ISO18000-6C |
| Frequency Range | 902-928MHZ ; 866-868MHZ |
| Chip | Alien higg3 |
| Chip capacity | EPC 96bit User memory 512bit |
| Chip life | Erasable 100,000 times |
| Size | 13*13*2MM 孔径 2MM |
| Operating | -20℃~100℃ |
| temperature | |
| Storage | -40℃~140℃ |
| temperature | |
| Weight | 0.7g |
| Material | FR4 |
| IP rating | IP68 |
| Reading distance | 1.5m(Attached to a metal surface, the test equipment |
| | is a fixed reader, 4W EIRP) |
| | 1m(Test equipment is R2000 module handheld, 30dbm |
| | power) |
| Polarization | Linear polarization |



direction

Conformance test: 100% pass Voyantic test

